

# OSYRIS DWX 5000



*Metalworking*

## UTILISATIONS

- **OSYRIX DWX 5000** is a water-repellent protective fluid, leaving an oily film on parts, providing medium-term protection.
- **OSYRIX DWX 5000** satisfies ISO standard 6743/8 (1987): category REE.
- Temporary storage in the mechanical engineering industry;
- Protection following surface treatment.

## ADVANTAGES

- Very high water-repellent capability.
- Medium protection from 8 to 10 months indoors and 3 months outdoors.
- **OSYRIX DWX 5000** is easily by soaking, spraying or with a brush owing to its high fluidity. The protective film can be removed using alkaline detergents or by solvents in the liquid or vapour phase.

TYPICAL CHARACTERISTICS	METHODS	UNITS	OSYRIS DWX 5000
Density	ISO 3675	kg/m <sup>3</sup>	0.805
Kinematic viscosity at 20 °C	ISO 3104	-	2.2
Flash point	ISO 2719	°C	36
Pour point	ISO 3016	°C	<-20
Ability to displace water	IP 178 (B)	score	yes

Above characteristics are mean values given as an information.

TOTAL LUBRIFIANTS  
Industrie & Spécialités

27 august 2001  
OSYRIS DWX 5000  
1/1

This lubricant used as recommended and for the application for which it has been designed does not present any particular risk.

A material safety data sheet conforming to the regulations in use in the E.C. can be obtained from your local commercial adviser or down loaded from [www.quick-fds.com](http://www.quick-fds.com).

