



TURMOSYNTHOIL GV 68



Date of issue: 19.01.2017

TURMOSYNTHOIL GV 68 is a synthetic oil for the food industry and the pharmaceutical industry.

TURMOSYNTHOIL GV 68 meets the CLP-requirements of DIN 51517.

TURMOSYNTHOIL GV 68 is NSF/H1 approved as lubricant for which an incidental contact with food technically cannot be avoided.

Special properties

- Ideal wear protection
- High oxidation resistance
- High ageing resistance
- Very good corrosion protection
- Expanded temperature range compared with mineral oil products
- Neutral towards elastomers and plastics
- Low foaming tendency

Product Characteristics	Value	Dimension	Norm / Standard
Colour	transparent, clear		
Density at 20°C	0,83	g/cm ³	DIN 51757
Operating temperature range	-40 to 120	°C	
Oil type	synthetic hydrocarbons		
Kinematic viscosity at 40°C	68	mm ² /s	DIN EN ISO 3104
Kinematic viscosity at 100°C	11	mm ² /s	DIN EN ISO 3104
Viscosity index (VI)	153		DIN ISO 2909
Pour point	-54	°C	DIN ISO 3016
Flash point	> 260	°C	DIN EN ISO 2592
Copper corrosion category 24 h / 100°C	1a		DIN EN 2160
FZG Scuffing load stage A/8,3/90	> 12		DIN 51354

Application

TURMOSYNTHOIL GV 68 is universally applicable for lubrication of compressors, gears, hydraulic systems and chains.

Packaging units

6 x 1 l bottles, 6 x 5 l canisters, 20 l canister, 60 l drum, 200 l drum



127129



The products are subject to continuous strict production controls and comply with our own factory specifications. A warranty for each case cannot be given, due to the variety of relevant factors. Therefore, we recommend the implementation of field tests. Herewith, any liability is expressly excluded.

LUBRICANT CONSULT GMBH · Gutenbergstrasse 13 · 63477 Maintal (Germany)
Tel: +49 (0) 6109 / 7650-0 · Fax: +49 (0) 6109 / 7650-51 · E-Mail: webmaster@lubcon.com · Internet: <http://www.lubcon.com>